



802.11ac-VHT40 26dB Bandwidth & 99% Bandwidth - Ant 0 / Ant 0 + 1


Channel 38 (5190MHz)




Channel 46 (5230MHz)




Channel 54 (5270MHz)




Channel 62 (5310MHz)




Channel 102 (5510MHz)




Channel 118 (5590MHz)




Channel 134 (5670MHz)




Channel 142 (5710MHz)



Channel 151 (5755MHz)




Channel 159 (5795MHz)




802.11ac-VHT80 26dB Bandwidth & 99% Bandwidth - Ant 0 / Ant 0 + 1


Channel 42 (5210MHz)




Channel 58 (5290MHz)




Channel 106 (5530MHz)




Channel 122 (5610MHz)



Channel 138 (5690MHz)



Channel 155 (5775MHz)



7.3. 6dB Bandwidth Measurement

7.3.1. Test Limit

The minimum 6dB bandwidth shall be at least 500 kHz.


7.3.2. Test Procedure used

KDB 789033 D02v02r01 - Section C.2

7.3.3. Test Setting

1. Set center frequency to the nominal EUT channel center frequency.
2. RBW = 100 kHz.
3. $VBW \geq 3 \times RBW$.
4. Detector = Peak.
5. Trace mode = max hold.
6. Sweep = auto couple.
7. Allow the trace to stabilize.
8. Measure the maximum width of the emission that is constrained by the frequencies associated with the two outermost amplitude points (upper and lower frequencies) that are attenuated by 6 dB relative to the maximum level measured in the fundamental emission.

7.3.4. Test Setup




7.3.5.Test Result

Product	G-140W-C	Temperature	24°C
Test Engineer	Lewis Huang	Relative Humidity	59%
Test Site	TR3	Test Date	2017/12/12


Test Mode	Data Rate / MCS	Channel No.	Frequency (MHz)	6dB Bandwidth (MHz)	Limit (MHz)	Result
Ant 0 / Ant 0 + 1						
802.11a	6Mbps	149	5745	15.78	≥ 0.5	Pass
802.11a	6Mbps	157	5785	15.52	≥ 0.5	Pass
802.11a	6Mbps	165	5825	15.71	≥ 0.5	Pass
802.11n-HT20	MCS0	149	5745	15.68	≥ 0.5	Pass
802.11n-HT20	MCS0	157	5785	16.31	≥ 0.5	Pass
802.11n-HT20	MCS0	165	5825	15.79	≥ 0.5	Pass
802.11n-HT40	MCS0	151	5755	35.23	≥ 0.5	Pass
802.11n-HT40	MCS0	159	5795	35.22	≥ 0.5	Pass
802.11ac-VHT20	MCS0	149	5745	15.38	≥ 0.5	Pass
802.11ac-VHT20	MCS0	157	5785	15.81	≥ 0.5	Pass
802.11ac-VHT20	MCS0	165	5825	16.27	≥ 0.5	Pass
802.11ac-VHT40	MCS0	151	5755	35.23	≥ 0.5	Pass
802.11ac-VHT40	MCS0	159	5795	35.24	≥ 0.5	Pass
802.11ac-VHT80	MCS0	155	5775	75.30	≥ 0.5	Pass

802.11a 6dB Bandwidth - Ant 0 / Ant 0 + 1


Channel 149 (5745MHz)



Channel 157 (5785MHz)




Channel 165 (5825MHz)




802.11n-HT20 6dB Bandwidth - Ant 0 / Ant 0 + 1


Channel 149 (5745MHz)



Channel 157 (5785MHz)




Channel 165 (5825MHz)




802.11n-HT40 6dB Bandwidth - Ant 0 / Ant 0 + 1

Channel 151 (5755MHz)




Channel 159 (5795MHz)




802.11ac-VHT20 6dB Bandwidth - Ant 0 / Ant 0 + 1


Channel 149 (5745MHz)



Channel 157 (5785MHz)




Channel 165 (5825MHz)




802.11ac-VHT40 6dB Bandwidth - Ant 0 / Ant 0 + 1

Channel 151 (5755MHz)




Channel 159 (5795MHz)



802.11ac-VHT80 6dB Bandwidth - Ant 0 / Ant 0 + 1

Channel 155 (5775MHz)



7.4. Output Power Measurement

7.4.1. Test Limit

For an indoor access point operating in the band 5.15-5.25 GHz, the maximum conducted output power over the frequency band of operation shall not exceed 1 W provided the maximum antenna gain does not exceed 6 dBi.

For the 5.25-5.35 GHz and 5.47-5.725 GHz bands, the maximum conducted output power over the frequency bands of operation shall not exceed the lesser of 250 mW (23.98dBm) or 11dBm +10 log (26dB BW).

For the band 5.725-5.85 GHz, the maximum conducted output power over the frequency band of operation shall not exceed 1 W (30dBm).

If transmitting antennas of directional gain greater than 6dBi are used, the maximum conducted output power shall be reduced by the amount in dB that the directional gain of the antenna exceeds 6dBi.


7.4.2. Test Procedure Used

KDB 789033D02v01r04- Section E)3)b) Method PM-G

7.4.3. Test Setting

Average power measurements were performed only when the EUT was transmitting at its maximum power control level using a broadband power meter with a pulse sensor. The power meter implemented triggering and gating capabilities which were set up such that power measurements were recorded only during the ON time of the transmitter. The trace was averaged over 100 traces to obtain the final measured average power.

7.4.4. Test Setup



7.4.5.Test Result

Power output test was verified over all data rates of each mode shown as below table, and then choose the maximum power output (gray marker) for final test of each channel.

Output power at various data rates for Ant 0 / Ant 0 + 1 port:

Test Mode	Bandwidth	Channel	Frequency (MHz)	Data Rate/ MCS	Average Power (dBm)
802.11a	20	36	5180	6Mbps	17.61
				24Mbps	17.23
				54Mbps	17.01
802.11n	20	36	5180	MCS0	18.64
				MCS3	18.31
				MCS7	18.02
802.11n	40	38	5190	MCS0	16.32
				MCS3	15.98
				MCS7	15.76
802.11ac	20	36	5180	MCS0	19.88
				MCS4	19.65
				MCS8	19.32
802.11ac	40	38	5190	MCS0	16.77
				MCS4	16.43
				MCS9	16.17
802.11ac	80	42	5210	MCS0	15.17
				MCS4	14.87
				MCS9	14.56



Product	G-140W-C	Temperature	24°C
Test Engineer	Dandy Li	Relative Humidity	59%
Test Site	TR3	Test Date	2017/12/10

Test Mode	Data Rate/ MCS	Channel No.	Freq. (MHz)	Ant 0 Average Power (dBm)	Ant 1 Average Power (dBm)	Total Average Power (dBm)	Average Power Limit (dBm)	Result
Ant 0 + 1								
11a	6Mbps	36	5180	17.61	17.26	20.45	≤ 30.00	Pass
11a	6Mbps	44	5220	19.67	17.87	21.87	≤ 30.00	Pass
11a	6Mbps	48	5240	19.57	17.68	21.74	≤ 30.00	Pass
11a	6Mbps	52	5260	17.12	17.02	20.08	≤ 23.98	Pass
11a	6Mbps	60	5300	17.63	16.89	20.29	≤ 23.98	Pass
11a	6Mbps	64	5320	17.14	16.87	20.02	≤ 23.98	Pass
11a	6Mbps	100	5500	17.15	16.57	19.88	≤ 23.98	Pass
11a	6Mbps	120	5600	17.74	17.32	20.55	≤ 23.98	Pass
11a	6Mbps	140	5700	17.02	17.66	20.36	≤ 23.98	Pass
11a	6Mbps	144	5720	17.06	17.45	20.27	≤ 23.98	Pass
11a	6Mbps	149	5745	22.33	22.86	25.61	≤ 30.00	Pass
11a	6Mbps	157	5785	22.70	22.73	25.73	≤ 30.00	Pass
11a	6Mbps	165	5825	21.48	22.38	24.96	≤ 30.00	Pass
11n-HT20	MCS0	36	5180	18.64	16.93	20.88	≤ 30.00	Pass
11n-HT20	MCS0	44	5220	19.66	18.46	22.11	≤ 30.00	Pass
11n-HT20	MCS0	48	5240	20.22	18.53	22.47	≤ 30.00	Pass
11n-HT20	MCS0	52	5260	16.82	16.25	19.55	≤ 23.98	Pass
11n-HT20	MCS0	60	5300	17.38	16.70	20.06	≤ 23.98	Pass
11n-HT20	MCS0	64	5320	17.02	16.61	19.83	≤ 23.98	Pass
11n-HT20	MCS0	100	5500	17.41	16.33	19.91	≤ 23.98	Pass
11n-HT20	MCS0	120	5600	16.74	16.58	19.67	≤ 23.98	Pass
11n-HT20	MCS0	140	5700	16.92	17.44	20.20	≤ 23.98	Pass
11n-HT20	MCS0	144	5720	17.08	17.36	20.23	≤ 23.98	Pass
11n-HT20	MCS0	149	5745	22.57	22.71	25.65	≤ 30.00	Pass
11n-HT20	MCS0	157	5785	21.77	22.47	25.14	≤ 30.00	Pass
11n-HT20	MCS0	165	5825	21.48	22.41	24.98	≤ 30.00	Pass

Test Mode	Data Rate/ MCS	Channel No.	Freq. (MHz)	Ant 0 Average Power (dBm)	Ant 1 Average Power (dBm)	Total Average Power (dBm)	Average Power Limit (dBm)	Result
11n-HT40	MCS0	38	5190	16.32	14.41	18.48	≤ 30.00	Pass
11n-HT40	MCS0	46	5230	21.13	17.58	22.72	≤ 30.00	Pass
11n-HT40	MCS0	54	5270	20.60	20.37	23.50	≤ 23.98	Pass
11n-HT40	MCS0	62	5310	17.31	16.61	19.98	≤ 23.98	Pass
11n-HT40	MCS0	102	5510	18.44	17.32	20.93	≤ 23.98	Pass
11n-HT40	MCS0	118	5590	20.33	20.18	23.27	≤ 23.98	Pass
11n-HT40	MCS0	134	5670	19.65	19.38	22.53	≤ 23.98	Pass
11n-HT40	MCS0	142	5710	19.86	20.85	23.39	≤ 23.98	Pass
11n-HT40	MCS0	151	5755	22.58	22.89	25.75	≤ 30.00	Pass
11n-HT40	MCS0	159	5795	22.14	23.03	25.62	≤ 30.00	Pass
11ac-VHT20	MCS0	36	5180	19.88	17.95	22.03	≤ 30.00	Pass
11ac-VHT20	MCS0	44	5220	20.88	18.90	23.01	≤ 30.00	Pass
11ac-VHT20	MCS0	48	5240	20.57	18.60	22.71	≤ 30.00	Pass
11ac-VHT20	MCS0	52	5260	16.59	18.45	20.63	≤ 23.98	Pass
11ac-VHT20	MCS0	60	5300	16.85	16.81	19.84	≤ 23.98	Pass
11ac-VHT20	MCS0	64	5320	17.36	16.62	20.02	≤ 23.98	Pass
11ac-VHT20	MCS0	100	5500	16.92	16.38	19.67	≤ 23.98	Pass
11ac-VHT20	MCS0	120	5600	16.99	16.62	19.82	≤ 23.98	Pass
11ac-VHT20	MCS0	140	5700	17.22	17.46	20.35	≤ 23.98	Pass
11ac-VHT20	MCS0	144	5720	16.39	17.34	19.90	≤ 23.98	Pass
11ac-VHT20	MCS0	149	5745	21.75	21.97	24.87	≤ 30.00	Pass
11ac-VHT20	MCS0	157	5785	21.26	21.65	24.47	≤ 30.00	Pass
11ac-VHT20	MCS0	165	5825	21.43	21.87	24.67	≤ 30.00	Pass
11ac-VHT40	MCS0	38	5190	16.77	15.23	19.08	≤ 30.00	Pass
11ac-VHT40	MCS0	46	5230	19.96	18.35	22.24	≤ 30.00	Pass
11ac-VHT40	MCS0	54	5270	20.83	19.75	23.33	≤ 23.98	Pass
11ac-VHT40	MCS0	62	5310	18.17	17.09	20.67	≤ 23.98	Pass
11ac-VHT40	MCS0	102	5510	18.02	17.53	20.79	≤ 23.98	Pass
11ac-VHT40	MCS0	118	5590	20.05	20.16	23.12	≤ 23.98	Pass
11ac-VHT40	MCS0	134	5670	18.91	18.86	21.90	≤ 23.98	Pass
11ac-VHT40	MCS0	142	5710	19.62	20.58	23.14	≤ 23.98	Pass
11ac-VHT40	MCS0	151	5755	21.29	22.05	24.70	≤ 30.00	Pass
11ac-VHT40	MCS0	159	5795	21.06	21.51	24.30	≤ 30.00	Pass

Test Mode	Data Rate/ MCS	Channel No.	Freq. (MHz)	Ant 0 Average Power (dBm)	Ant 1 Average Power (dBm)	Total Average Power (dBm)	Average Power Limit (dBm)	Result
11ac-VHT80	MCS0	42	5210	15.17	13.24	17.32	≤ 30.00	Pass
11ac-VHT80	MCS0	58	5290	17.10	15.89	19.55	≤ 23.98	Pass
11ac-VHT80	MCS0	106	5530	19.41	17.05	21.40	≤ 23.98	Pass
11ac-VHT80	MCS0	122	5610	21.01	19.65	23.39	≤ 23.98	Pass
11ac-VHT80	MCS0	138	5690	20.67	19.89	23.31	≤ 23.98	Pass
11ac-VHT80	MCS0	155	5775	19.52	19.42	22.48	≤ 30.00	Pass

Note: Total Average Power (dBm) = $10 \cdot \log\{10^{(\text{Ant 0 Average Power} / 10)} + 10^{(\text{Ant 1 Average Power} / 10)}\}$..

7.5. Transmit Power Control

7.5.1. Test Limit

The U-NII device is required to have the capability to operate at least 6 dB below the mean EIRP value of 30 dBm.


7.5.2. Test Procedure Used

KDB 789033 D02v01- Section E)3)b) Method PM-G

7.5.3. Test Setting

Average power measurements were performed only when the EUT was transmitting at its maximum power control level using a broadband power meter with a pulse sensor. The power meter implemented triggering and gating capabilities which were set up such that power measurements were recorded only during the ON time of the transmitter.

7.5.4. Test Setup



7.5.5. Test Result

A TPC mechanism is not required for systems with an e.i.r.p. of less than 500mW.

7.6. Power Spectral Density Measurement

7.6.1. Test Limit

For an indoor access point operating in the band 5.15-5.25 GHz, the maximum power spectral density shall not exceed 17 dBm in any 1 megahertz band.

For the band 5.725-5.85 GHz, the maximum power spectral density shall not exceed 30 dBm in any 500-kHz band.

If transmitting antennas of directional gain greater than 6dBi are used, the peak power spectral density shall be reduced by the amount in dB that the directional gain of the antenna exceeds 6dBi.


7.6.2. Test Procedure Used

KDB 789033 D02v02r01 - Section F

7.6.3. Test Setting

1. Analyzer was set to the center frequency of the UNII channel under investigation
2. Span was set to encompass the entire 26dB EBW of the signal.
3. RBW = 1MHz, if measurement bandwidth of Maximum PSD is specified in 500 kHz,
RBW = 100 kHz
4. VBW = 3MHz
5. Number of sweep points $\geq 2 \times (\text{span} / \text{RBW})$
6. Detector = power averaging (Average)
7. Sweep time = auto
8. Trigger = free run
9. Use the peak search function on the instrument to find the peak of the spectrum and record its value.
10. Add $10 \cdot \log(1/x)$, where x is the duty cycle, to the measured power in order to compute the average power during the actual transmission times (because the measurement represents an average over both the on and off times of the transmission). For example, add $10 \cdot \log(1/0.25) = 6$ dB if the duty cycle is 25 percent.
11. When the measurement bandwidth of Maximum PSD is specified in 500 kHz, add a constant factor $10 \cdot \log(500\text{kHz}/100\text{kHz}) = 6.99$ dB to the measured result.

7.6.4. Test Setup



7.6.5.Test Result

Product	G-140W-C	Temperature	22°C
Test Engineer	Lewis Huang	Relative Humidity	54%
Test Site	TR3	Test Date	2017/12/12
Test Item	Power Spectral Density (Band 1, Band 2A & Band 2C)		

Test Mode	Data Rate / MCS	Channel No.	Freq. (MHz)	Ant 0 PSD (dBm/ MHz)	Ant 1 PSD (dBm/ MHz)	Duty Cycle (%)	Total PSD (dBm/ MHz)	PSD Limit (dBm/MHz)	Result
11a	6Mbps	36	5180	7.69	5.72	86.97	10.43	≤ 16.99	Pass
11a	6Mbps	44	5220	8.84	6.50	86.97	11.44	≤ 16.99	Pass
11a	6Mbps	48	5240	8.53	6.47	86.97	11.24	≤ 16.99	Pass
11a	6Mbps	52	5260	7.49	6.64	86.97	10.70	≤ 10.99	Pass
11a	6Mbps	60	5300	7.48	6.43	86.97	10.60	≤ 10.99	Pass
11a	6Mbps	64	5320	7.17	6.49	86.97	10.46	≤ 10.99	Pass
11a	6Mbps	100	5500	7.22	7.01	86.97	10.73	≤ 10.99	Pass
11a	6Mbps	120	5600	7.47	6.97	86.97	10.84	≤ 10.99	Pass
11a	6Mbps	140	5700	6.48	7.25	86.97	10.50	≤ 10.99	Pass
11a	6Mbps	144	5720	6.61	7.12	86.97	10.49	≤ 10.99	Pass
11n-HT20	MCS0	36	5180	7.38	5.59	86.31	13.08	≤ 16.99	Pass
11n-HT20	MCS0	44	5220	9.04	7.52	86.31	13.52	≤ 16.99	Pass
11n-HT20	MCS0	48	5240	9.32	6.47	86.31	12.88	≤ 16.99	Pass
11n-HT20	MCS0	52	5260	6.98	6.47	86.31	10.23	≤ 10.99	Pass
11n-HT20	MCS0	60	5300	6.81	6.63	86.31	12.00	≤ 10.99	Pass
11n-HT20	MCS0	64	5320	6.68	6.45	86.31	11.77	≤ 10.99	Pass
11n-HT20	MCS0	100	5500	6.66	6.71	86.31	10.38	≤ 10.99	Pass
11n-HT20	MCS0	120	5600	7.27	6.70	86.31	10.37	≤ 10.99	Pass
11n-HT20	MCS0	140	5700	6.95	7.08	86.31	10.22	≤ 10.99	Pass
11n-HT20	MCS0	144	5720	6.54	7.24	86.31	10.33	≤ 10.99	Pass

Test Mode	Data Rate/ MCS	Channel No.	Freq. (MHz)	Ant 0 PSD (dBm/ MHz)	Ant 1 PSD (dBm/ MHz)	Duty Cycle (%)	Total PSD (dBm/ MHz)	PSD Limit (dBm/MHz)	Result
11n-HT40	MCS0	38	5190	2.72	1.18	75.85	6.23	16.99	Pass
11n-HT40	MCS0	46	5230	6.04	4.22	75.85	9.44	16.99	Pass
11n-HT40	MCS0	54	5270	4.98	5.58	75.85	9.50	10.99	Pass
11n-HT40	MCS0	62	5310	3.21	3.08	75.85	7.36	10.99	Pass
11n-HT40	MCS0	102	5510	4.23	4.15	75.85	8.40	10.99	Pass
11n-HT40	MCS0	118	5590	6.53	6.45	75.85	10.70	10.99	Pass
11n-HT40	MCS0	134	5670	5.73	5.51	75.85	9.83	10.99	Pass
11n-HT40	MCS0	142	5710	5.93	6.95	75.85	10.68	10.99	Pass
11ac-VHT20	MCS0	36	5180	8.42	6.42	86.32	11.18	16.99	Pass
11ac-VHT20	MCS0	44	5220	8.64	7.27	86.32	11.66	16.99	Pass
11ac-VHT20	MCS0	48	5240	9.46	7.42	86.32	12.21	16.99	Pass
11ac-VHT20	MCS0	52	5260	6.77	6.77	86.32	10.42	10.99	Pass
11ac-VHT20	MCS0	60	5300	6.97	6.39	86.32	10.34	10.99	Pass
11ac-VHT20	MCS0	64	5320	7.01	6.48	86.32	10.40	10.99	Pass
11ac-VHT20	MCS0	100	5500	6.73	6.60	86.32	10.31	10.99	Pass
11ac-VHT20	MCS0	120	5600	6.76	6.97	86.32	10.52	10.99	Pass
11ac-VHT20	MCS0	140	5700	6.56	6.74	86.32	10.30	10.99	Pass
11ac-VHT20	MCS0	144	5720	6.56	7.06	86.32	10.47	10.99	Pass
11ac-VHT40	MCS0	38	5190	2.85	1.23	76.07	6.31	16.99	Pass
11ac-VHT40	MCS0	46	5230	6.30	4.39	76.07	9.65	16.99	Pass
11ac-VHT40	MCS0	54	5270	6.62	6.28	76.07	10.65	10.99	Pass
11ac-VHT40	MCS0	62	5310	4.26	3.71	76.07	8.19	10.99	Pass
11ac-VHT40	MCS0	102	5510	4.83	4.96	76.07	9.09	10.99	Pass
11ac-VHT40	MCS0	118	5590	6.37	6.57	76.07	10.67	10.99	Pass
11ac-VHT40	MCS0	134	5670	4.65	5.34	76.07	9.21	10.99	Pass
11ac-VHT40	MCS0	142	5710	5.76	6.67	76.07	10.44	10.99	Pass
11ac-VHT80	MCS0	42	5210	-1.18	-3.46	61.22	2.97	16.99	Pass
11ac-VHT80	MCS0	58	5290	0.41	-0.41	61.22	5.16	10.99	Pass
11ac-VHT80	MCS0	106	5530	1.69	1.14	61.22	6.57	10.99	Pass
11ac-VHT80	MCS0	122	5610	2.52	2.74	61.22	7.77	10.99	Pass
11ac-VHT80	MCS0	138	5690	2.31	2.68	61.22	7.64	10.99	Pass

Note 1: When EUT duty cycle $\geq 98\%$, the total PSD = $10 \cdot \log\{10^{(\text{Ant 0 PSD}/10)} + 10^{(\text{Ant 1 PSD}/10)}\}$

Note 2: When EUT duty cycle $< 98\%$, the total PSD = $10 \cdot \log\{10^{(\text{Ant 0 PSD}/10)} + 10^{(\text{Ant 1 PSD}/10)}\} + 10 \cdot \log(1/\text{duty cycle})$

Product	G-140W-C	Temperature	22°C
Test Engineer	Dandy Li	Relative Humidity	54%
Test Site	TR3	Test Date	2017/12/12
Test Item	Power Spectral Density (Band 3)		


Test Mode	Data Rate/ MCS	Channel No.	Freq. (MHz)	Ant 0 PSD (dBm/100kHz)	Ant 1 PSD (dBm/100kHz)	Duty Cycle (%)	Constant Factor	Total PSD (dBm/500kHz)	Limit (dBm/500kHz)	Result
11a	6Mbps	149	5745	2.08	2.83	86.97	6.99	13.08	29.99	Pass
11a	6Mbps	157	5785	2.66	3.15	86.97	6.99	13.52	29.99	Pass
11a	6Mbps	165	5825	2.04	2.49	86.97	6.99	12.88	29.99	Pass
11n-HT20	MCS0	149	5745	2.45	2.67	86.31	6.99	13.20	29.99	Pass
11n-HT20	MCS0	157	5785	1.82	2.31	86.31	6.99	12.71	29.99	Pass
11n-HT20	MCS0	165	5825	1.00	2.40	86.31	6.99	12.40	29.99	Pass
11n-HT40	MCS0	151	5755	-1.27	-1.24	75.85	6.99	9.95	29.99	Pass
11n-HT40	MCS0	159	5795	-1.55	-0.37	75.85	6.99	10.28	29.99	Pass
11ac-VHT20	MCS0	149	5745	0.87	1.58	86.32	6.99	11.88	29.99	Pass
11ac-VHT20	MCS0	157	5785	0.94	1.58	86.32	6.99	11.91	29.99	Pass
11ac-VHT20	MCS0	165	5825	0.89	2.73	86.32	6.99	12.55	29.99	Pass
11ac-VHT40	MCS0	151	5755	-1.92	-1.20	76.07	6.99	9.64	29.99	Pass
11ac-VHT40	MCS0	159	5795	-1.95	-1.60	76.07	6.99	9.42	29.99	Pass
11ac-VHT80	MCS0	155	5775	-6.08	-4.90	61.22	6.99	6.68	29.99	Pass

Note 1: When EUT duty cycle $\geq 98\%$, Total PSD (dBm/500kHz) = $10 \cdot \log 10^{\left(\text{Ant 0 PSD}/10\right)} + 10^{\left(\text{Ant 1 PSD}/10\right)}$ (dBm/100kHz) + Constant Factor.


Note 2: When EUT duty cycle $< 98\%$, Total PSD (dBm/500kHz) = $10 \cdot \log \left\{ 10^{\left(\text{Ant 0 PSD}/10\right)} + 10^{\left(\text{Ant 1 PSD}/10\right)} \right\}$ (dBm/100kHz) + $10 \cdot \log(1/\text{duty cycle})$ + Constant Factor.

802.11a Power Spectral Density - Ant 0 / Ant 0 + 1


Channel 36 (5180MHz)




Channel 44 (5220MHz)




Channel 48 (5240MHz)




Channel 52 (5260MHz)




Channel 60 (5300MHz)




Channel 64 (5320MHz)




Channel 100 (5500MHz)




Channel 120 (5600MHz)




Channel 140 (5700MHz)




Channel 144 (5720MHz)




Channel 149 (5745MHz)



Channel 157 (5785MHz)




Channel 165 (5825MHz)




802.11n-HT20 Power Spectral Density - Ant 0 / Ant 0 + 1


Channel 36 (5180MHz)



Channel 44 (5220MHz)




Channel 48 (5240MHz)




Channel 52 (5260MHz)




Channel 60 (5300MHz)



Channel 64 (5320MHz)




Channel 100 (5500MHz)




Channel 120 (5600MHz)




Channel 140 (5700MHz)




Channel 144 (5720MHz)




Channel 149 (5745MHz)



Channel 157 (5785MHz)




Channel 165 (5825MHz)




802.11n-HT40 Power Spectral Density - Ant 0 / Ant 0 + 1


Channel 38 (5190MHz)



Channel 46 (5230MHz)




Channel 54 (5270MHz)



Channel 62 (5310MHz)



Channel 102 (5510MHz)



Channel 118 (5590MHz)

